WARNING
Westinghouse
Series C
Industrial
Circuit Breaker Frame
RD 65k
2500 AMP MAX
600 VAC
3 POLE
CAT. RD325T32W
50°C
STYLE 1485D10G02
Equipped With:
DIGITRIP 310 TRIP UNIT
RE92500L81
Available Rating Plugs:
25RE925T
25RE916T
25RE9127
25RE920T
25RE8125T
A25RE925T1
A25RE925T2
Interrupting Capacity – RMS Symmetrical Amps
IEC 947-2
Volts Amps
240 ~ 125k
480 ~ 65k
600 ~ 50k
~ = 50/60 Hz
Ue Icu kA Ics kA
240 ~ 125 53
380 ~ 65 33
415 ~ 65 33
Uimp 8 kV
Category A
Terminal Cat. No.
Wire Size
Conductor Material
Torque Lb. In.
TA1600RD
500 – 1000 (4)
CU/AL
550
T1600RD
1 – 600 (4)
CU ONLY
375
Accessories Installed
Shunt Trip
Auxiliary Switch
Under V. Release
Alarm / Lockout
Westinghouse Electric Corporation
Made in U.S.A.
R
B

Westinghouse
Series C
Industrial
Circuit Breaker
Frame
JD 25k
250 Amp Max.
600 VAC
Cat. JD3250F
Style 1491D81G03
3 Pole
Use With Trip Unit Cat.
Thermal Magnetic JT3-_-_T
Amps – 070, 090, 100, 125, 150, 175, 200, 225, 250
Seltronic Basic JS3-_-_T
Seltronic ASTD JS3-_-_TA
Amps – 125, 150
*Insert Amps To Complete
Modification Code
Terminal Cat. Information
Cu/Al Cu Only Size
TA250KB T250KB 4-350(1)
60/75°C Wire – 70,90,100 & 125 Amp Only
Made in KSA
On/I
Off/O
Ckt No.
JD/JDB Interrupting Capacity
Sym. Amps in kA
Volts kA
240~ 65
480~ 25
600~ 18
250 *DC 10
IEC 947 – 2(Icu)
Volts kA
220~ 65
240~ 65
380~ 35
415~ 30
440~ 25
500~ 20
250 *DC 10
*Thermal Magnetic Trip Unit Only
Use Outside Poles For DC
Suitable For Use On
Single Phase AC Circuits
~ = 50/60 Hz
Terminal Torque Values
Cat. Lb./in.
T250KB 180
TA250KB 275
Middle East Circuit Breaker Co.
Westinghouse Licensee
Thermal
Magnetic
Trip Unit
Magnetic (Im)
Multiples of In
Push to Trip
250 Amps 50 °C Cat. No. JT3250T